

CORTO

		185 N	210 N	270 N / 270 NC	310 N	270 FN
Dimensions						
Working width	m	1.85	2.10	2.65	3.05	2.65
Transport width	m	-	-	-	2.45	2.60
Power requirement						
Power required (from)	min. kW (HP)	29 (39)	33 (45)	41 (56)	51 (70)	37 (50)
Power required with conditioner (from)	min. kW (HP)	34 (46)	40 (54)	51 (70)	-	-
Mounting	Category	II	II	II	II	II
PTO shaft speed	rpm	540	540	540	1000	540 / 1000
PTO shaft speed (optional)	rpm	-	-	1000	-	750
Mower						
Mowing drums	qty	2	2	4	4	4
Blades per drum	qty	3	4	3	3	3
Mowing height	mm	36/42*	36/42*	36/42*	36/42*	36/42*
Mowing height wth additional glide plates	mm	+25	+25	+25	+25	+25
Pair of swathing discs		-	-	●***	○	●
Second pair of swathing discs		-	-	○***	○	○
Swath width						
Without conditioner, without swathing discs	mm approx.	800	900	-	2200	-
Without conditioner, single pair of swathing discs	mm approx.	-	-	1300	1500	1200
Without conditioner, with second pair of swathing discs	mm approx.	-	-	700	900	700
With conditioner	mm approx.	900	900	1350-2650	-	-
Automatic contour following						
Fore and aft	Degrees	-	-	-	-	20
Lateral	Degrees	-	-	-	-	12
Additional equipment, conditioner						
Conditioner speed	rpm	936	936	936	-	-
Optional	rpm	-	-	-	-	-
Tyres and weight						
Tyres		-	-	-	-	-
Weight	kg approx.	481	529	840	950	605
Weight with conditioner	kg approx.	626	674	1028	-	-
Crop spreader		-	-	● for NC	-	-

● Standard ○ Optional - Not available

* With additional spacer ring (○).

** Stepless height adjustment

*** Only for the N version.

**** Swath width depends on forage quantity and travel speed.

275 F Profil	290 FN	3100 FC	3100 F PROFIL	3100 FN PROFIL	3100 N / 3100 NC
2.65	2.82	3.05	3.05	3.05	3.05
2.60	2.76	3.00	3.00	3.00	3.00
37 (50)	45 (60)	51 (70)	51 (70)	51 (70)	51 (70)
-	-	60 (82)	-	-	60 (82)
II	II	II	II	II	II
1000	540 / 1000	540 / 1000	1000	1000	1000
-	750	750	-	-	-
4	4	4	4	4	4
3	3	3	3	3	3
30-52*	36/42*	30-52*	30-52*	36/42*	36/42*
+25	+25	+25	+25	+25	+25
●	●	○	●	●	●***
○	○	○	○	○	○***
-	-	-	-	-	-
1200	1350	1450	1450	1450	1500
700	800	900	950	950	900
-	-	1350	-	-	1000-1600
20	20	20	20	20	-
20	12	12	20	20	-
-	-	900	-	-	900
-	-	770	-	-	770
-	-	-	-	-	11.5/80-15.3 8 PR
780	630	810	820	820	1344
-	-	990	-	-	1604
-	-	-	-	-	-

CLAAS continually develops its products to meet customer requirements. This means that all products are subject to change without notice. All descriptions and specifications in this brochure should be considered as approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please refer to your nearest CLAAS dealer and their price list for local specification details. Some protective panels may have been removed for photographic purposes in order to present the function clearly. To avoid any risk of danger, never remove these protective panels yourself. In this respect, please refer to the relevant instructions in the operator's manual.