

| CORTO | | Front mowers | | |
|-------|--|---------------|-------|-------|
| | | 3200 F PROFIL | 310 F | 285 F |

| Mower | | | | |
|--|-------------|-----------|-----------|-----------|
| Working width | m | 3.05 | 3.05 | 2.82 |
| Transport width | m | 3.00 | 3.00 | 2.76 |
| Swath width without swathing discs | mm, approx. | – | – | – |
| Swath width with 1 pair of swathing discs | mm, approx. | 1100–1450 | 1100–1450 | 1000–1350 |
| Swath width with 2 pairs of swathing discs | mm, approx. | 900–1450 | 900–1450 | 800–1350 |
| Mowing drums | Qty | 4 | 4 | 4 |
| Blades/drum | Qty | 3 | 3 | 3 |
| Regular cutting height | mm | 42/30–52* | 42 | 42 |
| Cutting height with spacer ring (+6mm) | mm | 48/– | 48 | 48 |
| Cutting height with high-cut bottom disc (+25mm) | mm | 67/55–77* | 67 | 67 |
| Weight | kg, approx. | 820/830* | 750 | 700 |

| Tractor requirements | | | | |
|--------------------------|-------|--|-----------------------|-----------------------|
| Hitch category | Cat. | II | II | II |
| PTO shaft speed | rpm | 1000 | 540/1000 | 540/1000 |
| Optional PTO shaft speed | rpm | – | 750 | 750 |
| Hydraulic spool valves | | 1 x sa ⁽¹⁾ /1 x da ⁽²⁾ | 1 x sa ⁽¹⁾ | 1 x sa ⁽¹⁾ |
| Power requirement | kW/hp | 51/70 | 51/70 | 45/60 |

| Equipment | | | | |
|--|--|---|---|---|
| Spring suspension | | ● | ● | ● |
| ACTIVE FLOAT | | ○ | ○ | ○ |
| High-cut mowing disc | | ○ | ○ | ○ |
| Spacer ring | | ○ | ○ | ○ |
| Quick knife change | | ● | ● | ● |
| Without swathing discs | | – | – | – |
| Swathing discs | | ● | ● | ● |
| Additional swathing discs | | ○ | ○ | ○ |
| Hydraulic foldable protective covers | | ○ | – | – |
| Hydraulic transport locking device | | – | – | – |
| Hydraulic lift | | – | – | – |
| Parking device/rollers | | – | – | – |
| Warning signs with lighting | | ○ | ○ | ○ |
| Double mirror | | ○ | ○ | ○ |
| Infinitely variable cutting height setting | | ○ | ○ | ○ |

1 For ACTIVE FLOAT option
 2 For hydraulic protective covers option
 3 For hydraulic lift option
 * Sub-type with infinitely variable height adjustment

● Standard ○ Optional □ Available – Not available

CLAAS continually develops its products to meet customer requirements. This means that all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please refer to your nearest CLAAS dealer

| CORTO | | Rear mowers | | |
|-------|--|--------------|-----|-----|
| | | 3200 CONTOUR | 220 | 190 |

| Mower | | | | |
|--|-------------|-----------|------|------|
| Working width | m | 3.05 | 2.10 | 1.85 |
| Transport width | m | 2.05 | 1.95 | 1.80 |
| Swath width without swathing discs | mm, approx. | 2200 | 900 | 800 |
| Swath width with 1 pair of swathing discs | mm, approx. | 1100–1450 | – | – |
| Swath width with 2 pairs of swathing discs | mm, approx. | 900–1450 | – | – |
| Mowing drums | Qty | 4 | 2 | 2 |
| Blades/drum | Qty | 3 | 4 | 3 |
| Regular cutting height | mm | 42 | 42 | 42 |
| Cutting height with spacer ring (+6mm) | mm | 48 | 48 | 48 |
| Cutting height with high-cut bottom disc (+25mm) | mm | 67 | 67 | 67 |
| Weight | kg, approx. | 1050 | 590 | 540 |

| Tractor requirements | | | | |
|--------------------------|-------|-------------------------------|-----------------------|-----------------------|
| Hitch category | Cat. | II | II | II |
| PTO shaft speed | rpm | 1000 | 540 | 540 |
| Optional PTO shaft speed | rpm | – | – | – |
| Hydraulic spool valves | | 1 x sa ⁽¹⁾ /1 x da | 1 x sa ⁽³⁾ | 1 x sa ⁽³⁾ |
| Power requirement | kW/hp | 51/70 | 33/45 | 29/39 |

| Equipment | | | | |
|--|--|-----------------|-----------------|-----------------|
| Spring suspension | | – | ○ | ○ |
| ACTIVE FLOAT | | ● | – | – |
| High-cut mowing disc | | ○ | ○ | ○ |
| Spacer ring | | ○ | ○ | ○ |
| Quick knife change | | ● | ● | ● |
| Without swathing discs | | ● | ● | ● |
| Swathing discs | | ○ | – | – |
| Additional swathing discs | | ○ | – | – |
| Hydraulic foldable protective covers | | – | – | – |
| Hydraulic transport locking device | | ○ | – | – |
| Hydraulic lift | | – | ○ | ○ |
| Parking device/rollers | | ○/○ | – | – |
| Warning signs with lighting | | ○ | ○ | ○ |
| Double mirror | | 34 ⁴ | 34 ⁴ | 34 ⁴ |
| Infinitely variable cutting height setting | | ○ | ○ | ○ |

and their price list for local specification details. Some protective panels may have been removed to present the function more clearly in photographs. To avoid any risks, you should never remove these protective panels yourself. In this context, please refer to the relevant instructions in the operator's manual.