

LINER side swathers <sup>1</sup>		1900	1800 TWIN <sup>2</sup>	1700 TWIN <sup>2</sup>	1700	1600 TWIN <sup>2</sup>	1600	800 TWIN <sup>2</sup>	700 TWIN <sup>2</sup>	500 PROFIL	450	420	370	320	500 T	450 T
<b>Dual-rotor swathers</b>								<b>Single-rotor swathers</b>								
Mounting								Swinging drawbar / hitch	Swinging drawbar / hitch	Three-point	Three-point / swivelling head	Three-point / swivelling head	Three-point / swivelling head	Three-point / swivelling head	Swinging drawbar / hitch	Swinging drawbar / hitch
Hitch category		Cat. II	Cat. II	Cat. II	Cat. II	Cat. II	Cat. II	–	–	Cat. II	Cat. I + II	Cat. I + II	Cat. I + II	Cat. I + II	–	–
Working width	m (DIN)	8.05	7.45–8.40	6.70–7.85	6.60	6.20–6.90	6.20	4.00–7.50	3.50–6.30	4.80	4.50	4.20	3.70	3.20	4.80	4.50
Transport width																
With tine arms mounted	m	2.99	2.99	2.89/2.99	2.89/2.99	2.89/2.99	2.89/2.99	3.60	3.00	3.80 <sup>3</sup>	3.50 <sup>3</sup>	3.20 <sup>3</sup>	2.98 <sup>3</sup>	2.80	3.80 <sup>3</sup>	3.50 <sup>3</sup>
With tine arms removed	m	–	–	–	–	–	–	2.42	2.42	2.40	2.30	2.00	2.22	2.22	2.50	2.20
Transport height:																
With tine arms mounted	m	3.99	3.99	3.99	3.99	3.79	3.79	–	–	–	–	–	–	1.52	–	–
With tine arms removed	m	3.69	3.54	3.67	3.67	–	–	–	–	2.45	2.45	2.35	2.15	2.15	2.45	2.45
Parking length (transport position)	m	9.64	9.19	8.66	8.66	8.25	8.25	8.55	8.00	3.30	4.10	3.80	2.55	2.43	4.40	5.25
Weight approx.	kg	2590	2480	2220	2080	1950	1810	1620	1440	805	650	560	450	380	785	660
Rotors	Qty	2	2	2	2	2	2	2	2	1	1	1	1	1	1	1
Rotor diameter	m	3.80	3.50	3.20	3.20	2.90	2.90	3.50	2.90	3.80	3.50	3.20	2.90	2.65	3.80	3.50
Tine arms per rotor	Qty	14	12	12	12	11	11	12	11	14	12	12	11	8	14	12
Dual tines per arm set	Qty	4	4	4	4	4	4	4	4	4	4	4	3 (4 ○)	3	4	4
Tine diameter	mm	9.50	9.50	9.50	9.50	9.50	9.50	9.50	9.50	9.50	9.00	9.00	9.00	9	9.50	9.00
PROFIX tine arm bracket		●	●	●	●	–	–	●	●	●	●	●	–	–	●	●
Swath-laying position		left	left	left	left	left	left	left	left	left	left	left	left	left	left	left
Two-wheel rotor chassis		–	–	–	–	–	–	–	–	–	–	–	–	●	●	–
Four-wheel rotor chassis		●	●	●	●	●	●	●	●	●	●	●	○	○	●	●
Six-wheel rotor chassis		○	○	○	○	–	–	–	–	○	–	–	–	–	–	–
<b>Tyres</b>																
Rotor chassis	16×6.50-8 10 PR	2×4 (2×6 ○)	2×4 (2×6 ○)	2×4 (2×6 ○)	2×4 (2×6 ○)	2×4	2×4	–	–	2×4 (2×6 ○)	4	4	2 (4 ○)	2 (4 ○)	–	–
	18×8.50-8 6 PR	–	–	–	–	–	–	2×4	2×4	–	–	–	–	–	4	4
Main frame	10.00/75-15.3 10 PR	–	–	●	●	●	●	–	–	–	–	–	–	–	–	–
	380/55-17	●	●	–	–	–	–	–	–	–	–	–	–	–	–	–
	340/55-16	–	–	○	○	○	○	–	–	–	–	–	–	–	–	–
Fully floating suspension		●	●	●	●	●	●	● <sup>4</sup>	● <sup>4</sup>	●	–	–	–	–	–	–
<b>Drive systems</b>																
PTO speed	rpm	540	540	540	540	540	540	540	540	540	540	540	540	540	540	540
Single wide-angle PTO drive shaft		●	●	●	●	●	●	●	●	–	–	–	–	–	●	●
<b>Convenience</b>																
Spare wheel 16×6.50-8 10 PR		○	○	○	○	○	○	–	–	–	–	–	–	–	–	–
Spare wheel 18×8.50-8 6 PR		–	–	–	–	–	–	○	○	–	–	–	–	–	–	–
Wheel weights		○	○	○	○	○	○	–	–	–	–	–	–	–	–	–
Double wide-angle PTO drive shaft		–	–	–	–	–	–	○	○	–	–	–	–	–	–	–
TWIN function		–	●	●	–	●	–	●	●	–	–	–	–	–	–	–
Castor guide wheel		–	–	–	–	–	–	○	○	–	○	○	○	–	○	○
Hydraulic swath guard folding		○	○	○	○	○ <sup>6</sup>	○ <sup>6</sup>	○	○	○	○	○	–	–	○	○
Hydraulic rotor height adjustment		–	–	–	–	–	–	–	–	○	○	○	–	–	–	–
Warning sign		–	–	–	–	–	–	–	–	○	○	○	○	○	○	○
Illuminated warning sign		●	●	●	●	●	●	●	●	○	○	○	○	○	○	○
Parallelogram drawbar		–	–	–	–	–	–	●	○	–	–	–	–	–	○	○
Hydraulic spool valves		1×sa (+ 1×sa <sup>5</sup> ) 1×da	1×sa (+ 1×sa <sup>5</sup> ) 1×da	1×sa (+ 1×sa <sup>5</sup> ) 1×da	1×sa (+ 1×sa <sup>5</sup> ) 1×da	1×sa (1×da <sup>9</sup> )	1×sa (1×da <sup>9</sup> )	1×sa 1×da	1×sa 1×da	– (2×da <sup>5,7</sup> )	– (2×da <sup>5,7</sup> )	– (2×da <sup>5,7</sup> )	–	–	1×sa (1×da <sup>5</sup> )	1×sa (1×da <sup>5</sup> )

- Swath guard
- TWIN function (option) with additional swath guard for front rotor
- Swath guard and safety frame folded

- Rear only
- Hydraulic swath guard folding  
Hydraulic swath guard adjustment
- Hydraulic rotor height adjustment

CLAAS continually develops its products to meet customer requirements. This means that all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please refer to your nearest CLAAS dealer and their price list for local specification details. Some protective panels may have been removed to present the function more clearly in photographs. To avoid any risks, you should never remove these protective panels yourself. In this context, please refer to the relevant instructions in the operator's manual.

● standard ○ optional □ available – not available

● standard ○ optional □ available – not available

LINER central swathers		4000	3600	3100	2900	2800	2700	2600
------------------------	--	------	------	------	------	------	------	------

		Four-rotor swathers		Dual-rotor swathers				
Hitch category		Cat. III	Cat. II	Cat. II	Cat. II	Cat. II	Cat. II	Cat. II
Working width	m (DIN)	12.20–15.00	9.90–12.70	8.70–10.00	8.00–9.00	7.40–8.20	6.80–7.40	6.20–6.80
Swath width <sup>1</sup> approx.	m	1.50–2.60	1.20–2.30	1.50–2.60	1.20–2.40	1.20–2.20	1.20–2.00	1.10–1.80
Transport width								
With tine arms mounted	m	3.00	3.00	2.97	2.97	2.97	2.97	2.97
Transport height:								
With tine arms mounted	m	3.99	3.99 <sup>2</sup>	4.46	3.99	3.99	3.99	3.99
With tine arms removed	m	3.57	3.40	3.75	3.72	3.47	3.38	3.18
Parking length (transport position)	m	10.16	8.70	6.92	6.53	6.53	5.87	5.87
Rotors	Qty	4	4	2	2	2	2	2
Rotor diameter	m	3.80	3.30	4.20	3.80	3.50	3.20	2.90
Tine arms per rotor	Qty	14	12	14	14	12	12	11
Dual tines per arm set	Qty	4	4	5	4	4	4	4
Tine diameter	mm	9.5	9.5	9.5	9.5	9.5	9	9
PROFIX tine arm bracket		●	●	●	●	●	●	–
Swath-laying position		Centre	Centre	Centre	Centre	Centre	Centre	Centre
Four-wheel rotor chassis		● <sup>3</sup>	●	–	● <sup>3</sup>	● <sup>3</sup>	●	●
Six-wheel rotor chassis		○ <sup>4</sup>	–	● <sup>3</sup>	○	○	○	–
Fully floating suspension		●	●	●	●	●	●	●

#### Drive systems

PTO speed	rpm	540	540	540	540	540	540	540
Single wide-angle PTO drive shaft		●	●	●	●	●	●	●

#### Tyres

Rotor chassis								
16×6.50-8 10 PR		4×4	4×4	2×6	2×4	2×4	2×4	2×4
Main frame								
10.00/75-15.3 10 PR		–	–	–	–	2	2	2
500/55-20		–	○	–	–	–	–	–
620/40 R 22.5		2	○	–	–	–	–	–
380/55-17		–	2	2	2	○	–	–
Weight approx.	kg	5480	4600	2880	2250	2050	1900	1600

#### Convenience

Spare wheel 16×6.50-8 10 PR		○	○	○	○	○	○	○
Wheel weights		–	–	●	○	○	○	–
Individual rotor lift (three-way valve)		–	–	○	○	○	○	○
Electrohydraulic individual rotor lift		●	●	○	○	○	–	–
Electrohydraulic rotor height adjustment		○	○	○	○	○	–	–
LED working lights		○	○	–	–	–	–	–
Hydraulic spool valves		–	1×sa	1×sa	1×sa	1×sa	1×sa	1×sa
		1×sa + FR or LS	1×sa + FR or LS	1×da	1×da	1×da	–	–

1 Depending on forage harvest conditions and engine speed

2 For tyre variant 500/55-20

3 Front lateral suspension

4 For rear pair of rotors

● standard ○ optional □ available – not available