

Front attachment matrix.

Front attachment	LEXION 700					LEXION 600					TUCANO 500			TUCANO 400				TUCANO 300		AVERO		DOMINATOR		
	780	770	760	750	740	670	660	650	630	620	580	570	560	450	440	430	420	340	320	240	160		130	
CERIO cutterbars																								
CERIO 930	■	■	■	■	■	■	■	□			■	■	■	■	■									
CERIO 770	■	■	■	■	■	■	■	■	□	□	■	■	■	■	■	■	■	□	□					
CERIO 680						■	■	■			■	■	■	■	■	■	■	■	■	□	□			
CERIO 620									■	■	■	■	■	■	■	■	■	■	■	■	■	□	□	
CERIO 560									■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
Standard cutterbars																								
C 490													□	□	■	■	■	■	■	■	■	■	■	
C 450																							■	
C 430														□	□	□	■	■	■	■	■		■	
C 420																							■	
C 370																		□	□	■	■			
VARIO cutterbars																								
VARIO 1230	■ ¹	■ ¹	■ ¹	■ ¹		□ ¹																		
VARIO 1080	■	■	■	■	■	□	□	□																
VARIO 930	■	■	■	■	■	■	■	□			■	■	■	■	■									
VARIO 770	■	■	■	■	■	■	■	■	□	□	■	■	■	■	■	■	■	□	□	□				
VARIO 680						■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
VARIO 620									■	■	■	■	■	■	■	■	■	■	■	■	■	□		
VARIO 560									■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
VARIO 500													■	■	■	■	■	■	■	■	■	■	■	■
MAXFLEX cutterbars																								
MAXFLEX 1200	■ ¹	■ ¹	■ ¹	■ ¹		□ ¹																		
MAXFLEX 1050	■	■	■	■	■	■	■	■																
MAXFLEX 930	■	■	■	■	■	■	■	■			■	■	■	■	■									
MAXFLEX 770	□	□	□	□	□	■	■	■	□	□	■	■	■	■	■	■	■	□	□	□				
MAXFLEX 620						□	□	□	■	■	■	■	■	■	■	■	■	■	■	■	■			
MAXFLEX 560						□	□	□	■	■	■	■	■	■	■	■	■	■	■	■	■			
MAXFLO cutterbars																								
MAXFLO 1200	■ ¹	■ ¹	■ ¹	■ ¹		□ ¹																		
MAXFLO 1050	■	■	■	■	■	■	■	■			■	■	■	■	■									
MAXFLO 900	■	■	■	■	■	■	■	■			■	■	■	■	■									
Folding cutterbars																								
C 540						□	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
C 450						□	□	■	■	□	□	□	□	■	■	■	■	■	■	■	■	■	■	■

■ Recommended □ Not recommended

¹ TERRA TRAC only
² Not approved for LEXION MONTANA

Front attachment	LEXION 700					LEXION 600					TUCANO 500			TUCANO 400				TUCANO 300		AVERO		DOMINATOR			
	780	770	760	750	740	670	660	650	630	620	580	570	560	450	440	430	420	340	320	240	160		130		
CORIO 12-row																									
CORIO 1275 C CONSPEED	■	■	■ ²	■ ²	■																				
CORIO 1270 C CONSPEED	■	■	■ ²	■ ²	■																				
CORIO 8-row																									
CORIO 890 CONSPEED	■	■	■	■	■	■ ²	■	■	■	□	■	■	■	■	■										
CORIO 880 FC CONSPEED	■	■	■	■	■	■ ²	■	■	■	□	■	■	■	■	■										
CORIO 880 FC	■	■	■	■	■	■ ²	■	■	■	□	■	■	■	■	■										
CORIO 875 C CONSPEED	■	■	■	■	■	■ ²	■	■	■	□	■	■	■	■	■										
CORIO 875 FC CONSPEED	■	■	■	■	■	■ ²	■	■	■	□	■	■	■	■	■										
CORIO 875 C	■	■	■	■	■	■ ²	■	■	■	□	■	■	■	■	■										
CORIO 875 FC	■	■	■	■	■	■ ²	■	■	■	□	■	■	■	■	■										
CORIO 870 C CONSPEED	■	■	■	■	■	■ ²	■	■	■	■	■	■	■	■	■										
CORIO 870 FC CONSPEED	■	■	■	■	■	■ ²	■	■	■	■	■	■	■	■	■										
CORIO 870 C	■	■	■	■	■	■ ²	■	■	■	■	■	■	■	■	■										
CORIO 870 FC	■	■	■	■	■	■ ²	■	■	■	■	■	■	■	■	■										
CORIO 6-row																									
CORIO 690 CONSPEED											■ ²	■	■	■	■	■	■	■	■	■	■	■			
CORIO 680 FC CONSPEED											■ ²	■	■	■	■	■	■	■	■	■	■	■			
CORIO 680 FC											■ ²	■	■	■	■	■	■	■	■	■	■	■			
CORIO 675 C CONSPEED											■ ²	■	■	■	■	■	■	■	■	■	■	■			
CORIO 675 FC CONSPEED											■ ²	■	■	■	■	■	■	■	■	■	■	■			
CORIO 675 C											■ ²	■	■	■	■	■	■	■	■	■	■	■			
CORIO 675 FC											■ ²	■	■	■	■	■	■	■	■	■	■	■			
CORIO 670 C CONSPEED											■ ²	■	■	■	■	■	■	■	■	■	■	■			
CORIO 670 FC CONSPEED											■ ²	■	■	■	■	■	■	■	■	■	■	■			
CORIO 670 C											■ ²	■	■	■	■	■	■	■	■	■	■	■			
CORIO 670 FC											■ ²	■	■	■	■	■	■	■	■	■	■	■			
CORIO 5-row																									
CORIO 575 C																□	□	□	□	□	□	■	■		
CORIO 570 C																□	□	□	□	□	□	■	■		
CORIO 4-row																									
CORIO 475 C																						■	■		
CORIO 470 C																						■	■		
CORIO 475 C ¹																							■		
CORIO 470 C ¹																							■		
SWATH UP																									
SWATH UP 450	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■			
SUNSPEED																									
SUNSPEED 16-70	■	■	■ ²	■ ²	■	■ ²	■	■																	
SUNSPEED 12-75	■	■	■ ²	■ ²	■	■ ²	■	■	■ ²	■	■	■	■	■	■	■	■	■	■	■	■	■			
SUNSPEED 12-70	■	■	■ ²	■ ²	■	■ ²	■	■	■ ²	■	■	■	■	■	■	■	■	■	■	■	■	■			
SUNSPEED 8-75													■	■	■	■	■	■	■	■	■	■	■	■	
SUNSPEED 8-70													■	■	■	■	■	■	■	■	■	■	■	■	

Please note that these recommendations are not valid for all regions. The regional road traffic regulations must be observed. The front attachment matrix may vary as a result of differing climatic conditions or cultivation methods.

The availability of individual combine harvester models depends on the applicable emissions standard for the country concerned and can therefore vary subject to national regulation.

Front attachments		VARIO cutterbars								CERIO cutterbars				Standard cutterbars				Folding cutterbars			
		VARIO 1230	VARIO 1050	VARIO 930	VARIO 770	VARIO 680	VARIO 620	VARIO 560	VARIO 500	CERIO 930	CERIO 770	CERIO 680	CERIO 620	CERIO 560	C 490	C 450 ¹	C 430	C 420 ¹	C 370	C 540	C 450
Effective cutting width	mm	12270	10740	9220	7696	6781	6172	5562	4953	9220	7696	6781	6172	5562	4920	4550	4320	4240	3710	5460	4550
Effective cutting width	ft.	41.00	35.25	30.25	25.25	22.25	20.25	18.25	16.25	30.25	25.25	22.25	20.25	18.25	16.14	14.93	14.17	13.91	12.17	17.91	14.93
Drive on both sides		●	●	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	●	●
Drive on one side		–	–	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	–	–
Dividers, folding		●	●	●	●	●	●	●	●	●	●	●	●	●	●	–	●	–	–	●	●
Dividers, height adjust. without tools		●	●	●	●	●	●	●	●	●	●	●	●	●	–	–	–	–	–	–	–
Spacing of knife bar to intake auger (min. / max.)	mm	493 / 1134	493 / 1134	493 / 1134	493 / 1134	493 / 1134	493 / 1134	493 / 1134	493 / 1134	579	579	579	579	579	545	560	560	580	545	560	560
Knife divided		●	●	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	●	●
Knife undivided		–	–	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	–	–
MULTIFINGER intake auger		●	●	●	●	●	●	●	●	●	●	●	●	●	●	–	●	–	●	●	●
Reel and auger bearing divided		●	●	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	●	●
Reel and auger bearing undivided		–	–	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	–	–
Crop lifters		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Intake auger diameter (ext. / int.)		660 / 420	660 / 420	660 / 420	660 / 420	660 / 420	660 / 420	660 / 420	660 / 420	660 / 420	660 / 420	660 / 420	660 / 420	660 / 420	580 / 380	580 / 380	580 / 380	580 / 380	580 / 380	580 / 380	580 / 380
Replacement knife		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
possible adjustment range, hydraulic	mm	700	700	700	700	700	700	700	700	–	–	–	–	–	–	–	–	–	–	–	–
possible adjustment range, manual	mm	–	–	–	–	–	–	–	–	200	200	200	200	200	–	–	–	–	–	–	–
Weight (without rapeseed equipment)	kg	4055	3665	2989	2557	2334	2224	2093	1941	2824	2419	2140	2040	1926	1300	1080	1120	1000	940	2100	1980

Automated cutterbar control

CONTOUR	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	–	○	–	○	○	○
AUTO CONTOUR	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	–	○	–	○	○	○
Automatic parking position	●	●	●	●	●	●	●	●	●	●	●	–	–	–	–	–	–	–	–	–	–
Automatic operating position	●	●	●	●	●	●	●	●	●	●	●	–	–	–	–	–	–	–	–	–	–
Reel speed control	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Automatic reel height	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Automatic reel levelling	●	●	●	●	●	●	●	●	●	–	–	–	–	–	–	–	–	–	–	–	–
Automatic table control	●	●	●	●	●	●	●	●	●	–	–	–	–	–	–	–	–	–	–	–	–
LASER PILOT	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	–	○	–	○	○	○

Rice equipment

Intake auger wear protection	–	–	○	○	○	○	○	○	○	○	○	○	○	○	○	–	○	○	–	–	–
Rice cutting system	–	–	○	○	○	○	○	○	○	○	○	○	○	○	○	–	○	○	–	–	–
Twin knife system	–	–	–	–	–	–	–	–	–	–	–	–	–	–	○	–	○	–	–	–	–

Rapeseed equipment

Rapeseed table	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–
Rapeseed knives	○	○	○	○	○	○	○	○	○	–	–	–	–	–	–	–	–	–	–	–	–
Rapeseed plates	●	●	●	●	●	●	●	●	●	–	–	–	–	–	–	–	–	–	–	–	–
Spacing: knife bar – intake auger	mm	1134	1134	1134	1134	1134	1134	1134	1134	–	–	–	–	–	–	–	–	–	–	–	–
possible adjustment range with rapeseed equipment		150	150	150	150	150	150	150	150	–	–	–	–	–	–	–	–	–	–	–	–

¹ DOMINATOR only

Front attachments		MAXFLO cutterbars			MAXFLEX cutterbars					
		1200	1050	900	1200	1050	930	770	620	560
Effective cutting width	mm	11960	10440	9220	11960	10440	9220	7696	6172	5563
Effective cutting width	ft.	40.00	35.00	30.25	40.00	35.00	30.25	25.25	20.25	18.25
Drive on both sides		●	●	●	●	●	–	–	–	–
Drive on one side		–	–	●	–	–	●	●	●	●
Vertical flexibility of knife bar	mm	–	–	–	180	180	180	180	180	180
Knife divided		●	●	–	●	●	–	–	–	–
Knife undivided		–	–	–	–	–	●	●	●	●
MULTIFINGER intake auger		●	●	●	●	●	●	●	●	●
Reel and auger bearing divided		●	●	–	●	●	–	–	–	–
Reel and auger bearing undivided		–	–	●	–	–	●	●	●	●
Crop lifters		●	●	●	○	○	○	○	○	○
Replacement knife		●	●	●	●	●	●	●	●	●
Rapeseed knives		○	○	○	–	–	–	–	–	–
Additional cross augers		○	○	○	–	–	–	–	–	–
Weight	kg	3500	3200	2715	3750	3395	2671	2289	1885	1768

Automated cutterbar control

CONTOUR	○	○	○	○	○	○	○	○	○
AUTO CONTOUR	○	○	○	○	○	○	○	○	○
Automatic parking position	–	–	–	–	–	●	●	●	●
Automatic operating position	–	–	–	–	–	●	●	●	●
Reel speed control	●	●	●	●	●	●	●	●	●
Automatic reel height	●	●	●	●	●	●	●	●	●
Automatic reel levelling	–	–	–	–	–	–	–	–	–
LASER PILOT	○	○	○	○	○	○	○	○	–

Front attachments		SWATH UP 450	SUNSPEED				
			16-70	12-75	12-70	8-75	8-70
Effective pick-up width	mm	4523					
Effective pick-up width	ft.	14.84					
Drive on one side		●					
No. of pick-up fingers		392					
Weight	kg	1366					
Number of rows			16	12	12	8	8
Row width	cm		70	75	70	75	70
Shuttle length	mm		1800	1800	1800	1800	1800
Shuttle width	mm		311	337	311	337	311
Shuttle gap adjustment range	mm		30-50	30-50	30-50	30-50	30-50
Reel and auger bearing undivided			–	–	●	●	●
Reel and auger bearing divided			●	–	–	–	–
reel: undivided, auger: divided			–	●	–	–	–
Replacement knife			●	●	●	●	●
Weight	kg		3300	2820	2638	1800	1720
Reel speed control			●	●	●	●	●
Automatic reel height			●	●	●	●	●
Automatic reel levelling			–	–	–	–	–

As CLAAS continually develops its products to meet customers' requirements, all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please consult your nearest CLAAS dealer and their price list for local specification details. Some protective panels may have been removed for photographic purposes in order to present the function clearly. To avoid hazards, never remove these protective panels yourself. Please refer to the relevant instructions in the operator's manual in this regard. All technical specifications relating to engines are based on the European emission regulation standards: Stage. Any reference to the Tier standards in this document is intended solely for information purposes and ease of understanding. It does not imply approval for regions in which emissions are regulated by Tier.

Front attachments	CORIO CONSPEED 12-row		CORIO CONSPEED 8-row						CORIO CONSPEED 6-row						CORIO 8-row					CORIO 6-row					CORIO 5-row		CORIO 4-row							
	1275 C	1270 C	890 C	880 FC	875 C	875 FC	870 C	870 FC	690 C	680 FC	675 C	675 FC	670 C	670 FC	880 FC	875 C	875 FC	870 C	870 FC	680 FC	675 C	675 FC	670 C	670 FC	575 C	570 C	475 C	470 C	475 C ¹	470 C ¹				
Number of rows	12	12	8	8	8	8	8	8	6	6	6	6	6	6	8	8	8	8	8	6	6	6	6	6	5	5	4	4	4	4				
Row width	cm	75	70	90	80	75	75	70	70	90	80	75	75	70	70	80	75	75	70	70	80	75	75	70	70	75	70	75	70	75	70			
Transport position – rigid		●	●	●	–	●	–	●	–	●	–	●	–	●	–	●	–	●	–	●	–	●	–	●	–	●	●	●	●	●	●			
Transport position – folding		–	–	–	●	–	●	–	●	–	●	–	●	–	●	–	●	–	●	–	●	–	●	–	●	–	–	–	–	–	–			
Horizontal chopper		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●			
Working width	m	9.78	8.63	7.17	6.53	6.18	6.18	5.83	5.83	5.37	4.93	4.68	4.68	4.43	4.43	6.53	6.18	6.18	5.83	5.83	4.93	4.68	4.68	4.43	4.43	3.93	3.73	3.18	3.03	3.18	3.03			
Transport width	m	9.78	8.63	7.17	3.35	6.18	3.00	5.83	3.00	5.37	3.35	4.68	3.00	4.43	3.00	3.35	6.18	3.00	5.83	3.00	3.35	4.68	3.00	4.43	3.00	3.93	3.73	3.18	3.03	3.18	3.03			
Stubble breaker		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
MONTANA mounting kit ²		–	–	–	○	○	○	○	○	–	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○		
Sunflower kit		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○		
Raised hoods		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
Laid maize augers		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
Shear bar kit		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
Sprocket for intake auger to increase speed		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
Electrohydraulic snapping plate adjustment		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Intake auger loss protection		●	●	●	●	●	●	●	●	●	●	●	●	●	●	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Road transport protection incl. lighting and safety bar		–	–	–	●	–	●	–	●	–	●	–	●	–	●	–	●	–	●	–	●	–	●	–	●	–	–	–	–	–	–	–	–	
Support for trailer		○	○	○	–	○	–	○	–	○	–	○	–	○	–	–	○	–	○	–	–	○	–	○	–	○	○	○	○	○	○	○	○	
Weight	kg	3820	3700	2750	2990	2590	2910	2510	2855	2150	2355	2030	2295	2030	2295	3110	2710	3030	2630	2950	2445	2120	2385	2120	2385	1770	1770	1475	1475	1460	1460			
Automated cutterbar control																																		
AUTO CONTOUR		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
AUTO PILOT		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

¹ Only for DOMINATOR 130

² Suitable for LEXION 760 / 750 and 630 MONTANA, not suitable for LEXION 670 MONTANA