

VARIANT		485 RC PRO	465 RC PRO	480 RF/RC	460 RF/RC	470 RF	450 RF
Hitching							
PTO shaft speed	rpm	1000/540	1000 (○) /540	540 or 1000	540 or 1000	540	540
Power requirement	kW/hp	75/102	75/102	75/102	75/102	68/92	68/92
Main drive and drive chains		Heavy Duty, 1 ¼"	Heavy Duty, 1 ¼"	Standard, 1"	Standard, 1"	Standard, 1"	Standard, 1"
Central chain lubrication		●	●	●	●	●	●
Central lubrication system		○	○	○	○	–	–
Ball hitch		○	○	○	○	–	–
Hydraulic connection							
Single-acting spool valve for pick-up lift		●	●	●	●	●	●
Dual-acting spool valve for tailgate rams		●	●	●	●	●	●
Additional dual-acting spool valve for PRO cutting floor		●	●	●	●	–	–
Pick-up							
Width	m	2.10	2.35 (○)	2.10	2.35 (○)	2.10	2.10
DIN pick-up width	m	1.90	2.15 (○)	1.90	2.15 (○)	1.90	1.90
Ground-contour following with two oscillating castor guide wheels		●	●	●	●	○	○
Roller crop press		○	○	○	○	○	○
Double-roller crop press		○	○	○	○	–	–
Crop feed							
Forced feed with		Heavy Duty ROTO CUT	Heavy Duty ROTO CUT	ROTO FEED / ROTO CUT	ROTO FEED / ROTO CUT	ROTO FEED	ROTO FEED
Number of knives (with ROTO CUT)		14	14	14	14	–	–
Hydraulically lowerable PRO cutting floor		○	○	○	○	–	–
Variable baling chamber							
High-strength endless belts	Qty.	4	4	4	4	4	4
Belt speed	m/s	3	3	2.9	2.9	2.9	2.9
Soft-core device, pressure and diameter adjustable		●	●	●	●	●	●
Supplementary belt drive		●	●	●	●	–	–
Moisture sensor		○	○	○	○	–	–
Heavy Duty concept		●	●	–	–	–	–
Bale chamber dimensions							
Width	m	1.20	1.20	1.20	1.20	1.20	1.20
Diameter	m	0.90–1.80	0.90–1.55	0.90–1.80	0.90–1.55	0.90–1.80	0.90–1.55
Operation							
OPERATOR		●	●	●	●	●	●
COMMUNICATOR II		○	○	○	○	○	○
ISOBUS cables		○	○	○	○	○	○

VARIANT		485 RC PRO	465 RC PRO	480 RF/RC	460 RF/RC	470 RF	450 RF
Wrapping							
NEW guiding plate		●	●	●	●	●	●
Net wrapping with automatic start		●	●	●	●	●	●
Number of net turns, selectable		9 settings	9 settings	9 settings	9 settings	9 settings	9 settings
Dual twine wrapping with automatic wrapping start		○	○	○	○	●	●
CLAAS Covered net wrapping		○	○	○	○	○	○
CLAAS Covered XW net wrapping		○	○	○	○	○	○
Number of twine turns, selectable		10 settings	10 settings	10 settings	10 settings	10 settings	10 settings
Tyres							
11.5/80 15.3 10PR		–	–	–	–	●	●
15.0/55 R 17		●	●	●	●	○	○
19.0/45 R 17		○	○	○	○	○	○
500/50 17 F+		○	○	○	○	–	–
Pick-up oscillating castor guide wheels 16/6.50-8 10PR		●	●	●	●	●	●
Air brakes		○	○	○	○	–	–
Dimensions and weights							
Length with bale ramp	m	4.68	4.68	4.68	4.68	4.68	4.68
Width with 15.0/55 R 17 tyres	m	2.49	2.49	2.49	2.49	2.49	2.49
Width with 19.0/45 R 17 tyres	m	2.66	2.66	2.66	2.66	2.66	2.66
Width with 500/50 17 F+ tyres	m	2.67	2.67	2.67	2.67	–	–
Height	m	2.99–3.03	2.79–2.83	2.99–3.03	2.79–2.83	2.99–3.03	2.99–3.03
Weight	kg	3730	3530	3650	3400	3310	3170



15.0/55-17 10PR 19.0/45-17 10PR 500/50-17 F+

CLAAS continually develops its products to meet customer requirements. This means that all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please refer to your nearest CLAAS dealer and their price list for local specification details. Some protective panels may have been removed for photographic purposes in order to present the function clearly. To avoid any risk of danger, never remove these protective panels yourself. In this respect, please refer to the relevant instructions in the operator's manual.

● Standard ○ Optional – Unavailable