

DISCO <sup>1</sup>	3600 FRC MOVE	3600 FC MOVE	3600 F MOVE	3200 FRC MOVE	3200 FC MOVE	3200 F MOVE	3600 FRC PROFILE	3600 FC PROFILE	3600 F PROFILE	3200 FRC PROFILE	3200 FC PROFILE	3200 F PROFILE	3150 F
--------------------	---------------	--------------	-------------	---------------	--------------	-------------	------------------	-----------------	----------------	------------------	-----------------	----------------	--------

**Front mowers**

**Dimensions and weights**

		3600 FRC MOVE	3600 FC MOVE	3600 F MOVE	3200 FRC MOVE	3200 FC MOVE	3200 F MOVE	3600 FRC PROFILE	3600 FC PROFILE	3600 F PROFILE	3200 FRC PROFILE	3200 FC PROFILE	3200 F PROFILE	3150 F
Working width	m	3.40	3.40	3.40	3.00	3.00	3.00	3.00	3.40	3.40	3.00	3.00	3.00	3.00
Hitch category		II	II	II	II	II	II	II	II	II	II	II	II	II
PTO speed	rpm	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)
Transport width	m	3.40	3.40	3.40	3.00	3.00	3.00	3.40	3.40	3.40	3.00	3.00	3.00	3.00
Machine height	m	–	–	–	–	–	–	–	–	–	–	–	–	–
Weight (according to conditioner)	approx. kg	1420	1390	1060	1250	1220	970	685	1195	870	1040	1010	775	685

**Mower**

MAX CUT mower bar <sup>2</sup>		●	●	●	●	●	●	●	●	●	●	●	●	●
ACTIVE FLOAT suspension		● <sup>3</sup>	● <sup>3</sup>	● <sup>3</sup>	● <sup>3</sup>	● <sup>3</sup>	● <sup>3</sup>	○ <sup>3</sup>	○ <sup>3</sup>	○ <sup>3</sup>	○ <sup>3</sup>	○ <sup>3</sup>	○ <sup>3</sup>	○ <sup>3</sup>
Discs (2 knives per disc)		8	8	8	7	7	7	8	8	8	7	7	7	7
Quick blade change		●	●	●	●	●	●	●	●	●	●	●	●	●

**Conditioner**

Conditioner speed	rpm	950	900 / 770	–	950	900 / 770	–	950	900 / 770	–	950	900 / 770	–	–
-------------------	-----	-----	-----------	---	-----	-----------	---	-----	-----------	---	-----	-----------	---	---

**Hydraulics**

Hydraulic spool valves		1 sa (+1 da4 + 1sa3)						(1 da4 + 1sa3)					
------------------------	--	----------------------	--	--	--	--	--	----------------	--	--	--	--	--

**Equipment**

Hydraulically foldable protective side covers		○ <sup>4</sup>	○ <sup>4</sup>	○ <sup>4</sup>	○ <sup>4</sup>	○ <sup>4</sup>	○ <sup>4</sup>	○ <sup>4</sup>	○ <sup>4</sup>	○ <sup>4</sup>	○ <sup>4</sup>	○ <sup>4</sup>	○ <sup>4</sup>	–
Wide crop spreader		–	–	–	–	–	–	–	–	–	–	–	–	–
Adjustable swathing plates		●	●	–	●	●	–	●	●	–	●	●	–	–
Outside swathing disc		–	–	● (2 x)	–	–	● (1 x)	–	–	● (2 x)	–	–	● (1 x)	● (1 x)
High-cut skids		○	○	○	○	○	○	○	○	○	○	○	○	○
Twin high-cut skids		○	○	○	○	○	○	○	○	○	○	○	○	–
Wear skids		○	○	○	○	○	○	○	○	○	○	○	○	○
Bar protection device (for intensive use conditions)		○	○	○	○	○	–	–	○	○	○	○	–	–
Warning signs with lighting		○ <sup>5</sup>	○ <sup>5</sup>	○ <sup>5</sup>	○ <sup>5</sup>	○ <sup>5</sup>	○ <sup>5</sup>	○ <sup>5</sup>	○ <sup>5</sup>	○ <sup>5</sup>	○ <sup>5</sup>	○ <sup>5</sup>	○ <sup>5</sup>	○
Double mirror		○	○	○	○	○	○	○	○	○	○	○	○	○
Hydraulic transport locking device		–	–	–	–	–	–	–	–	–	–	–	–	–
Mechanical breakback protection		–	–	–	–	–	–	–	–	–	–	–	–	–

<sup>1</sup> C = tine conditioner, FC = roller conditioner, F = front, T = trailed, no suffix = without conditioner

<sup>2</sup> Standard mowing height 40 mm (continuously adjustable, 30–70 mm)

<sup>3</sup> 1 x sa required for setting the ACTIVE FLOAT pressure

<sup>4</sup> 1 x da required for the hydraulic folding of the protective cover

<sup>5</sup> Folding

DISCO large-scale mowers <sup>1</sup>		9400 C DUO	9200 C AUTOSWATHER	1100 RC BUSINESS	1100 C BUSINESS	9200 C BUSINESS	9200 BUSINESS	9200 RC CONTOUR	9200 C CONTOUR	9200 CONTOUR	8500 RC CONTOUR	8500 C CONTOUR	8500 CONTOUR	1100 TREND	9200 TREND	8500 TREND
<b>Dimensions and weights</b>																
Working width <sup>2</sup>	m	9.10/8.90	9.10/8.90	9.60–10.70 <sup>3</sup>	9.40–10.70 <sup>3</sup>	9.10/8.90	9.10/8.90	9.10/8.90	9.10/8.90	9.10/8.90	8.30/8.10	8.30/8.10	8.30/8.10	9.60–10.70 <sup>3</sup>	9.10/8.90	8.30/8.10
Hitch category		III	III	III	III	III	III (II)	III	III	III (II)	III	III	III (II)	III	III (II)	III (II)
PTO speed	rpm	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)
Transport width	m	2.95	2.95	2.95	2.95	2.95	2.95	2.95	2.95	2.95	2.95	2.95	2.95	2.95	2.95	2.95
Machine height	m	3.81	3.89	3.79	3.79	3.89	3.89	3.89	3.89	3.89	3.64	3.64	3.64	3.79	3.64	3.64
Weight	approx. kg	2800	3590 (+ 40 <sup>4</sup> )	3570	3520	2360	2010	2600	2320	1980	2300	2100	1830	2600	1940	1790
<b>Mower</b>																
MAX CUT mower bar <sup>5</sup>		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
ACTIVE FLOAT suspension		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Discs (2 knives per disc)		2×8	2×8	2×9	2×9	2×8	2×8	2×8	2×8	2×8	2×7	2×7	2×7	2×9	2×8	2×7
Quick blade change		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
<b>Conditioner</b>																
Conditioner speed	rpm	910	1100 / 990	940	910	910	–	940	910	–	940	910	–	–	–	–
<b>Hydraulics</b>																
Hydraulic spool valves		LS (or 1×sa + free return) + 1×sa for P2						1×sa + 1×da						2×da (+ 1×sa)	2×sa (+ 1×sa <sup>6</sup> )	
<b>Operation</b>																
ISOBUS-compatible		●	●	●	●	●	●	●	●	●	●	●	●	–	–	–
EASY on board		○	○	○	○	○	○	–	–	–	–	–	–	–	–	–
COMMUNICATOR II		○	○	○	○	○	○	–	–	–	–	–	–	–	–	–
OPERATOR		–	–	–	–	○	○	○	○	○	○	○	○	–	–	–
ISOBUS cable		○	○	○	○	○	○	○	○	○	○	○	○	–	–	–
Hectare count for OPERATOR		–	–	–	–	○	○	○	○	○	○	○	○	–	–	–
<b>Optional</b>																
Hydraulically foldable protective side covers		●	○	●	●	●	●	○	○	○	–	–	–	●	–	–
Wide crop spreader		○	●	–	○	○	–	–	○	–	–	○	–	–	–	–
Adjustable swathing plates		●	●	●	●	●	–	●	●	–	●	●	–	–	–	–
Outside swathing disc		–	–	–	–	–	●	–	–	●	–	–	●	○	○	○
Swathing belt cover		–	○	–	–	–	–	–	–	–	–	–	–	–	–	–
Slope control		–	●	–	–	–	–	–	–	–	–	–	–	–	–	–
High-cut skids		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Twin high-cut skids		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Wear skids		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Bar protection device (for intensive use conditions)		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Warning signs with lighting		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Hydraulic transport locking device		●	●	●	●	●	●	●	●	●	●	●	●	●	–	–
Breakback protection																
Mechanical		–	–	–	–	–	–	●	●	●	●	●	●	–	●	●
Hydraulic		●	●	●	●	●	●	–	–	–	–	–	–	●	–	–

<sup>1</sup> C = tine conditioner, RC = roller conditioner, no suffix = without conditioner

<sup>2</sup> Working width including front mower 3600 FRC / FC / F PROFIL, 3200 FRC / FC / F PROFIL, 3150 F

<sup>3</sup> According to front mower used, infinitely variable adjustment

<sup>4</sup> Central lubrication

<sup>5</sup> Standard cut height 40 mm (infinitely variable adjustment 30–70 mm)

<sup>6</sup> For individual lifting function

CLAAS continually develops its products to meet customer requirements. This means that all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please refer to your nearest CLAAS dealer and their price list for local specification details. Some protective panels may have been removed to present the function more clearly in photographs. To avoid any risks, you should never remove these protective panels yourself. In this context, please refer to the relevant instructions in the operator's manual.